

mod. PR 1300



Modello PR 1300 - PR 800.

Macchine applicatrici di film protettivo

Macchine studiate per l'applicazione di film protettivo removibile su pannelli piani o sagomati.

Le macchine della serie PR possono essere dotate di rulliere di diverse dimensioni in base alle esigenze, possono essere inserite in una linea di produzione a carico automatico, oppure manuale, hanno la capacità di lavorare ad alte velocità con una costante e precisa applicazione del film protettivo, più corto, a filo o più lungo rispetto al bordo del pannello, molto indicata nei processi di verniciatura e di imballo.

Le macchine possono essere prodotte in varie dimensioni in base alle esigenze del cliente.



Model PR 1300 - PR 800.

Protective film application machines

Machines designed to apply removable protective film on flat or shaped panels. PR series machines may be realized with different roller conveyor dimension, can be fitted in an automatic or manual loading production line.

These units offer high-speed operations with regular and precise application of protective film, shorter and flush with or longer with respect to the panel edge, mainly during painting processes, and packing.

Machines may be realized in different dimensions, regarding to customers requirement.



www.viganomario.it

Via Alessandro Volta, 62/A
22060 AROSIO (Co) Italy
Tel. +39.031.763201
Fax +39.031.763611
info@viganomario.it

mod. PR 1300

mod. PR 800



Caratteristiche tecniche PR 1300, PR 800

- Struttura in acciaio elettrosaldato
- Altezza piano di lavoro regolabile -- 900 mm. +/- 10 mm
- Larghezza utile di lavoro -- 1.300 mm 800 mm.
- Spessore massimo di lavoro -- 80 mm.
- Trasporto motorizzato con rulli d.mm. 60
- Motorizzazioni sup./inf. controllati da encoder.
- Rulliera motoriz. in entrata da -- 1200, 1500, 2000 mm. con trasporto a rulli d.mm.60 rivestiti in gomma completa di guida pannelli a rullini, scorrevole su tutta la larghezza regolabile tramite volantino.
- Quadro elettrico, pulsantiera comandi a bordo macchina completa di pannello operatore touch screen.
- Velocità variabile regolabile -- da 10 a 30 mt./min.
- Salita-discesa motorizzata.
- Albero portabobine a bandiera espansibile -- d. 75 mm.
- Bancale macchina a rulli in uscita da -- 500 mm.
- Carter di protezione apribile.
- Rulliera motorizzata in uscita da -- 1200, 1500, 2000 mm. con trasporto a rulli d.mm.60 rivestiti in gomma e rettificati.
- Normativa CE
- Colori -- RAL 9002 - 5015 - 1007
- Voltaggio -- 400 V 50 Hz
- Peso PR 800 -- 580 Kg.
- Ingombri PR 800 -- 2000 x 1100 x h. 1200 mm.
- Peso PR 1300 -- 700 Kg.
- Ingombri PR 1300 -- 2600 x 1100 x h. 1200 mm.

Technical Specifications PR 1300, PR 800

- Electrically-welded steel structure
- Adjustable worktable height -- 900 mm +/- 10 mm
- Working width -- 1.300 mm 800 mm
- Maximum working thickness -- 80 mm
- Motorized conveyor with rollers dia. -- 60 mm.
- Upper/lower motorisation controlled by encoder
- Motorized roller conveyor at infeed -- 1200, 1500, 2000 mm. conveyor with 60 mm. dia. ground rollers covered with rubber complete with roller panel guide, sliding along the width.
- Control panel, push-button on board machine complete with touch screen operator panel.
- Adjustable variable speed -- from 10 to 30 mt./min.
- Displayed motorized up/down movement.
- Expanding spindle swinging reel -- diam. 75 mm.
- Roller machine bed at outfeed -- 500 mm.
- Openable protection hood.
- Motorized roller conveyor at outfeed -- 1200, 1500, 2000 mm.
- CE-mark
- Colours -- RAL 9002 - 5015 - 1007
- Voltage -- 400 V 50 Hz.
- Weight -- PR 800 -- 580 kg.
- Overall dimensions -- PR 800 -- 2000 x 1100 x h. 1200 mm.
- Weight -- PR 1300 -- 700 kg.
- Overall dimensions PR 1300 -- 2600 x 1100 x h. 1200 mm.



www.viganomario.it

Via Alessandro Volta, 62/A
22060 AROSIO (Co) Italy
Tel. +39.031.763201
Fax +39.031.763611
info@viganomario.it