PSE6100





Automatic stretch wrappers that can wrap palletized loads and be integrated into production lines. They are designed to function with all load types without requiring any manual operation. These machines are completely customizable with a wide range of options and accessories that facilitate the perfect solution for your production requirements and work environment.

PSE6100



PERFORMANCE

Output up to 60 pallets/hours

Pallet Maximum Sizes 1200 x 1200 mm

Load Maximum Height 2400 mm

Load Maximum Weight 2000 kg

MAIN FEATURES

Film Tension Control

Film Cutting

Thermal Blade

Hotwelding on load

Pre-stretching Relation

Platform Turning
Speed Control

Reel Carriage
Speed Control

Film Maximum Width 500 mm

Film Maximum Width 260 mm

Powered Roller
Platform

PLATFORM

Turning Device plataform

Turning Speed 21 RPM

Diameter 1900 mm

Height 450 mm

Conveyor Width 940/1340 mm

WEIGHT & SIZES

Weight 900 kg
L 2860 mm

Sizes W 1900 mm

H 3000 mm

UTILITIES

Pneumatics 6 bar

Consumption 120 l/cycle

Electrics 230/400V III+N+T

Consumption 3 kW/h

OPTIONS

| Wrapper Height | up to 3400 mm |
|---|---------------|
| Platform Diameter | up to 2500 mm |
| Load Maximum Weight | Max. 3000 kg |
| Powered Top Platen to stabilise load | √ |
| COVERMATIC Top Film Sheet Dispenser | 1 |
| Blade Film Cutting | √ |
| Safety Fencing | 1 |
| Film Stringer | √ |
| Raised Legs on Base | √ |
| Double Rell Support | |
| Adaptation to different working environments and temperatures | √ |
| Stainless Steel version | √ |
| ANFID Tape Dispenser | |
| RFID Label Reader | √ |
| Jumbo Reels | 1 |